

600 Series Card Counter Specifications

Model	Application	Metric	Inches
Permanent Setting Security Counters:			
620	High value cards	0.61mm-0.86mm	0.024"-0.034"
625	High value, white core cards, count through shrink film packaging	0.61mm-0.86mm	0.024"-0.034"
670	High value, opaque cards and clear cards	0.61mm-0.86mm	0.024"-0.034"
Adjustable Counters:			
640	Adjustable pitch	0.25mm-1.65mm	0.010"-0.065"
650	Thin cards	0.13mm-0.56mm	0.005"-0.022"
Variable Material Counters:			
632	Rounded edge material such as inserts/outserts	1.02mm-6.10mm	0.040"-0.240"
632E	Envelopes	1.02mm-5.08mm	0.040"-0.200"
Secure Counts in Cartridges:			
612	CR80 Cards in Cartridges	0.61mm-0.86mm	0.024"-0.034"
Physical dimension (except the 612):		711mm (28") W x 279mm (11") H x 292mm (11.5") D	
Shipping dimension (except the 612):		864mm (34") W x 432mm (17") H x 457mm (18") D	
Physical dimension for the 612:		330mm (13") W x 840mm (33") H x 230mm (9") D	
Shipping dimension for the 612:		965mm (38") W x 279mm (11") H x 508mm (20") D	
Length of Stack Tray (except for 612):		450mm	18"
612: Cartridge size needs to be specified when ordering.			
Physical weight (except the 612):		15Kg	33 Pounds
Shipping weight (except the 612):		19Kg	42 Pounds
Physical weight for the 612:		20Kg	45 Pounds
Shipping weight for the 612:		21Kg	47 Pounds
Power Supply:		100-240VAC, 50/60 HZ	612: 120 VAC, 2 Amp, 50/60 HZ

Supplied Accessories: Power Cord & Instruction Manual (Export models configured to receive country's electrical requirements.)

Accessories by request (except 612): Footswitch and Dust Cover

A600.04

